## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

09-228858

(43) Date of publication of application: 02.09.1997

51)Int.CI.

F02D 15/02

F02B 75/04 F02B 75/32

F16C 3/04

F16H 21/20

F16H 21/34

21)Application number : **08-061932** 

(71)Applicant: HONDOU JUTAKU:KK

22) Date of filing:

24.02.1996


(72)Inventor: SHIGEO YOSHIHIRO

## **54) RECIPROCATING ENGINE**

## 57) Abstract:

ROBLEM TO BE SOLVED: To make the side thrust force of a piston small, and reduce friction force caused by a reciprocal movement by mounting a bridge to a crank shaft, connecting a connecting rod with one end of the bridge, and connecting the end of a rocking arm rocking around a stationary shaft with the other end.

OLUTION: One end part of a bridge 4 the center part of which is rotatably supported by the eccentric shaft 7 of a crank shaft 6, is connected 5 with the lower end part of a connecting rod 3 mounted to a piston 1 reciprocated within a cylinder 2, and the other end of the ridge 4 is connected 10 with a rocking arm 9 rocked around a shaft 8. The reciprocal movement of the piston 1 thereby allows the bridge 4 to e rocked through the movement of the connecting rod 3 and the rocking motion of the rocking arm 9, and also allows the crank shaft 6 to be thereby rotated. In this place, the locus A of the lower end shaft 5 of the connecting rod 3 is to describe roughly an ellipse shape, and side



of the connecting rod 3 is to describe roughly an ellipse shape, and side thrust force is prevented from bei developed in the piston 1, so that sliding friction force against the cylinder 2 is thereby lessened.

## **LEGAL STATUS**

[Date of request for examination]

20.05.2002

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application